

PRODUCTS



Full screen



Half screen

Mobile control LED display+APP+cloud



Multiple installations

Suitable for hanging, wall mounted, base standing, bracket standing and creative installation



ADD: Building A, Hengyi Industrial Park, No. 19 Tianliao Road, Guangming New District, Shenzhen, China
 Cell: (+86)-159 99616652
 Fax: (+86)-755-27380982
 Hot-Line: (+86)755-27387271
 Email: sales@led-star.com
 Website: http://www.led-star.com



Hot Electronics Co., Ltd
Trustworthy Quality From The East

Wi-Fi Intelligent Led Advertising Board

Professional Manufacturer of LED display



Product Features:

- Adopt new Wi-Fi control technology, more energy saving and environmental friendly compared with traditional led screen.
- Standard Wi-Fi interface, which is easy and practical to access to all kinds of wireless network 4G+3G+2G+Wi-Fi, and USB support.
- Attractive & Convenient design, no assembly and easy to use for the End user.
- High brightness & Waterproof. Brightness can reach to 5500cd/m²

1. Realistic image and wide angle viewing



From the prospect of advertising, led advertising board combines the advantages of traditional back lit box media and television media, and also a perfect combination of printing advertising and video advertising. With realistic and smooth effect, some led advertising boards can only approach viewing angle of 120°, but we can make it at 160°. Even if view from the side, it will not be distorted, which increased the attention and arrival rate of the advertisement effectively.

2. Play content in variety of forms

The professional led advertising board can not only support a very rich playback format, but also be capable of variety of pictures, video clips, movies and other formats of film source played at anytime conveniently.



3. Flexible operation and Area extension

Commercial advertisement of the customer can be flexibly switched at any time with the central control system. And the advertising area can be randomly extended by seamless stitching.

4. Advantages compared with LCD

Compared with the LCD display, LED display has higher brightness, ultra-thin, lower power consumption and perfect visual effects. It can show perfectly even in bright places.



Wi-Fi Intelligent Led Advertising Board--Indoor

Pixel pitch	P2.5	P3
LED Shape	SMD 3 in 1	SMD 3 in 1
LED Configuration	1R1G1B	1R1G1B
Module Size	160mm*160mm	192mm*192mm
Drive Method	1/32	1/32
Display Size	640*1920mm	576*1920mm
Display Resolution	256*768	192*640
Module Number	4*12	3*10
Brightness	1000cd /m ²	1000cd/m ²
Viewing Angle	H/V 160/160	H/V 160/160
Max power consumption	976w/m ²	880w/m ²
Ave power consumption	600w/m ²	570w/m ²
Working Voltage	220V/110V	220V/110V
Frame Frequency	60 85 HZ	60 85 HZ
Refresh Rate	1920Hz	1920Hz
Date Transmission	CAT 5/Optic Fiber	CAT 5/Optic Fiber
Image Source	S Video PAL/NTSC	S Video PAL/NTSC
Format	Video Compatibility	Video Compatibility
	DVI VGA composite	DVI VGA composite
Working Temperature	20 65	20 65
Life Span	100 000Hours	100 000Hours
IP Rate	IP 54	IP 54


Note: The regular size in the table is for the full-screen advertising display. The price will adjust as the size changed

Front Maintenance

Led magnetic modules front access, and be fixed on the back of the modules with 4-10pcs magnets.



1. Insert the spanner between the gap of modules
2. Take out the modules from the cabinet slightly.



Wi-Fi Intelligent Led Advertising Board--Outdoor

Pixel pitch	P4	P5
LED Shape	SMD 3 in 1	SMD 3 in 1
LED Configuration	1R1G1B	1R1G1B
Module Size	256mm*128mm	320mm*160mm
Drive Method	1/8	1/8
Display Size	768*1920mm	640*1920mm
Display Resolution	192*480	128*384
Module Number	3*15	2*12
Brightness	5500cd /m ²	5500cd/m ²
Viewing Angle	H/V 160/160	H/V 160/160
Max power consumption	1176w/m ²	976w/m ²
Ave power consumption	750w/m ²	650w/m ²
Working Voltage	220V/110V	220V/110V
Frame Frequency	60 85 HZ	60 85 HZ
Refresh Rate	1440Hz	1440Hz
Date Transmission	CAT 5/Optic Fiber	CAT 5/Optic Fiber
Image Source	S Video PAL/NTSC	S Video PAL/NTSC
Format	Video Compatibility	Video Compatibility
	DVI VGA composite	DVI VGA composite
Working Temperature	20 65	20 65
Life Span	100 000Hours	100 000Hours
IP Rate	IP 65	IP 65

Note: The regular size in the table is for the full-screen advertising display. The price will adjust as the size changed

Front Maintenance

It's easy for installation and maintenance, taking only a few seconds to disassemble by using the hexagon spanner.

