

cases


Indoor P2.5 Project in KSA

Project Size:
32 cabinets
For: TV Station
Project Time:
March, 2016



Outdoor P6 for Australia

Project Size:
around 24sqm
For: Events Company
Project Time: 2013



Hot Electronics Co.,Ltd
Trustworthy Quality From The East

Rental Series

Professional Manufacturer of LED display



ADD: Building A, Hengyi Industrial Park, No. 19 Tianliao Road, Guangming New District, Shenzhen, China

Cell: (+86)-159 99616652

Fax: (+86)-755-27380982

Hot-Line: (+86)755-27387271

Email: sales@led-star.com

Website: http://www.led-star.com



Rental Series --Indoor

- ★ Light weight
- ★ Good Heat Dissipation
- ★ Low Power Consumption
- ★ Convenient Installation
- ★ Easy Move

Rental Series --Outdoor


- ★ Light weight
- ★ Waterproof: IP65
- ★ Time-saving Installation
- ★ High Brightness
- ★ Easy Move

Full front and rear installation and maintenance

1. Front maintenance: modules and power box can be easily dismantled via the maintenance tool



2. Rear maintenance: the magnetic power box cover can be opened with 2 seconds, maintenance efficiency is much higher



Rental Series--Indoor Die-casting Aluminum

Pixel Pitch(mm)	2	2.5	2.6	2.97	3.91	4.81
LED Configuration	SMD1010	SMD1515	SMD1515	SMD2121	SMD2121	SMD2121
Module Dimension	256*128	250*250	250*250	250*250	250*250	250*250
Module Resolution	128*64	100*100	96*96	84*84	64*64	52*52
Cabinet Dimension	512*512	500*500	500*500	500*500	500*500	500*500
Cabinet Resolution	256*256	200*200	192*192	168*168	128*128	104*104
Viewing Angle(H/V)	140/140	140/140	140/140	140/140	140/140	140/140
Brightness(Cds/m ²)	>1200	>1200	>1200	>1200	>1200	>1200
Refresh Rate(Hz)	1920-3840	1920-3840	1920-3840	1920-3840	1920-3840	1920-3840
Gray Scale(Bit)	14	14	14	14	14	14
Power Consumption (Max/Avg W/m ²)	400/150	400/150	400/150	400/150	400/150	400/150
Ip Rate(Front/Rear)	30/54	30/54	30/54	30/54	30/54	30/54
Working Voltage(V)	110/220	110/220	110/220	110/220	110/220	110/220
Working Temperature	-20-65°C	-20-65°C	-20-65°C	-20-65°C	-20-65°C	-20-65°C
Working Humidity	10%-95%	10%-95%	10%-95%	10%-95%	10%-95%	10%-95%



Rental Series-- Outdoor Die-casting Aluminum

Pixel Pitch(mm)	2.97	3.91	4.81	5.95	6.25
LED Configuration	SMD1921	SMD1921	SMD2525	SMD3535	SMD3535
Module Dimension	250*250	250*250	250*250	250*250	250*250
Module Resolution	84*84	64*64	52*52	42*42	40*40
Cabinet Dimension	500*500	500*500	500*500	500*500	500*500
Cabinet Resolution	168*168	128*128	104*104	84*84	80*80
Viewing Angle(H/V)	140/140	140/140	140/140	140/140	140/140
Brightness(Cds/m ²)	>5000	>5000	>5000	>5000	>5000
Refresh Rate(Hz)	1920-3840	1920-3840	1920-3840	1920-3840	1920-3840
Gray Scale(Bit)	14	14	14	14	14
Power Consumption (Max/Avg W/m ²)	400/150	400/150	400/150	400/150	400/150
Ip Rate(Front/Rear)	65/65	65/65	65/65	65/65	65/65
Working Voltage(V)	110/220	110/220	110/220	110/220	110/220
Working Temperature	-20-65°C	-20-65°C	-20-65°C	-20-65°C	-20-65°C
Working Humidity	10%-95%	10%-95%	10%-95%	10%-95%	10%-95%

Multiple installation ways available

